



Loytape Adhesive Tapes Product Brochure

CORPORATE OFFICE:



LOYTAPE INDUSTRIES SDN BHD (122768-U)

1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia.

☎ +604-390 7049 📠 +604-399 3030

✉ stick2us@loytape.com.my 🌐 www.loytape.com.my

For Trade Enquiries, Please Contact Any of Our Sales Offices

KUALA LUMPUR

31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.

☎ +603-9200 8199 📠 +603-9200 7990/8990

✉ sales-kl@loytape-marketing.com.my

PENANG

1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600 Perai,
Seberang Perai, Penang.

☎ +604-390 7049 📠 +604-399 7561

✉ sales-pg@loytape-marketing.com.my

JOHOR BAHRU

11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor.

☎ +607-355 9968 📠 +607-355 9967

✉ sales-jb@loytape-marketing.com.my

IPOH

10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.

☎ +605-536 5916 📠 +605-536 2717

✉ sales-ipoh@loytape-marketing.com.my

STICK 2 US!



A Subsidiary of W T K Holdings Berhad

Our Brands:



ISO 9001:2015
CERTIFIED TO
REGISTRATION NO. AT 19427



CELLULOSE TAPE

PRODUCT DESCRIPTION


- Manufactured from 100 % cellulose film which is a wood based product of regenerated pulp
- Highly transparent and has a pressure sensitive rubber adhesive system

FEATURES / APPLICATIONS

- Suitable for hamper and gift wrappings, sealing of plastic bags, small and light weight boxes
- Suitable for application as antistatic tape
- Environmental friendly and biodegradable
- Easy tear and can read through

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	550g/25mm
Holding Power	1440 mins
Total Thickness	0.044mm/0.049mm



HIGH TEMPERATURE MASKING TAPE

MKT-03, MKT-03Y, MKT-05, MKT-05Y, MKT-06

PRODUCT DESCRIPTION

- Soft crepe backing with natural rubber cured adhesive gives excellent holding strength to prevent lifting

FEATURES / APPLICATIONS

- Specially for high temperature automotive spray painting and bandoleering for electronic industry
- Good paint resistance (resist seep through)
- No tacky residue left on surface when removed

TECHNICAL CHARACTERISTICS :-

Grade	MKT-03, MKT-03Y	MKT-05, MKT-05Y	MKT-06
Peel Adhesion to Steel	750g/25mm	850g/25mm	920g/25mm
Total Thickness	0.145mm	0.155mm	0.165mm
Heat Resistance	100°C for 1 hour	150°C for 1 hour	160°C for 1 hour

COLORS AVAILABLE ● ●



WATER REPELLENT MASKING TAPE

MKT-30WP

PRODUCT DESCRIPTION

- Water repellent crepe backing with natural rubber cured adhesive gives excellent holding strength to prevent lifting

FEATURES / APPLICATIONS

- Strong water repellent for high performance automotive applications
- No tacky residue left on surface when removed

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	700g/25mm
Total Thickness	0.155mm
Heat Resistance	150°C for 1 hour

COLORS AVAILABLE ● ● ●



UV RESISTANT MASKING TAPE MKT-29

PRODUCT DESCRIPTION

- Good UV resistant crepe backing with solvent acrylic adhesive gives moderate holding strength to prevent lifting

FEATURES / APPLICATIONS

- Suitable for outdoor masking where UV resistance is required
- Clean removal without surface damage after exposure to direct sunlight

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	200g/25mm
Total Thickness	0.155mm

UV RESISTANT
● 7 days outdoor
● 14 days outdoor
● 30 days outdoor



GENERAL PURPOSE MASKING TAPE MKT-01, MKT-01E

PRODUCT DESCRIPTION

- Soft crepe backing with natural rubber adhesive gives excellent holding strength to prevent lifting

FEATURES / APPLICATIONS

- Suitable for carton sealing, bundling and for general masking purpose
- No tacky residue left on surface when removed

TECHNICAL CHARACTERISTICS :-

Grade	MKT-01	MKT-01E
Peel Adhesion to Steel	600g/25mm	600g/25mm
Total Thickness	0.135mm	0.130mm
Heat Resistance	80°C for 1 hour	60°C for 1 hour



GUMMED PAPER TAPE (PLAIN & PRINTED)

REINFORCED GUMMED PAPER TAPE (PLAIN & PRINTED)

PRODUCT DESCRIPTION


- Gummed Paper Tape is kraft paper backing coated with water based adhesive for ecologically friendly carton sealing
- Reinforced Gummed Paper Tape is made from cross-ply fabric reinforced paper tape coated with water based adhesive that offers very high set adhesive and paper strength when used

FEATURES / APPLICATIONS

- Gummed Paper Tape is suitable for low to medium duty packaging use only
- Reinforced Gummed Paper Tape is suitable for heavy duty paper carton sealing
- Available in printed form for security, advertising and handling instruction

TECHNICAL CHARACTERISTICS :-

Grade	Gummed Paper Tape	Reinforced Gummed Paper Tape
Dry Tack	350g/25mm	350g/25mm
Total Thickness	0.120mm	0.130mm



ALUMINIUM FOIL TAPE

PRODUCT DESCRIPTION

- Soft tempered aluminium foil backing with strong thermal resistant of solvent acrylic adhesive ensures tight binding

FEATURES / APPLICATIONS

- Suitable for sealing of air conditioning ducting system, cold storage insulation and temporary sealing of gaps
- Good moisture resistance

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	500g/25mm
Total Thickness	0.060mm

COLORS AVAILABLE



CLOTH TAPE

PRODUCT DESCRIPTION


- A polyethylene laminated cloth backing coated with rubber adhesive designed for heavy packing process

FEATURES / APPLICATIONS

- Suitable for book binding, heavy duty carton box packaging, cold storage sealing, repair vinyl seat cushions, plastic tarps, canvas, etc
- Water proof, hand tearable and easy to apply

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	700g/25mm
Total Thickness	0.250mm



DOUBLE SIDED TISSUE TAPE

PRODUCT DESCRIPTION


- Manufactured from cotton tissue coated with solvent acrylic adhesive

FEATURES / APPLICATIONS

- Suitable for adhesion and conversion of advertising and decorative objects, sample cards, cardboard and foam
- Medium duty splicing for paper carton boxes

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	1000g/25mm
Total Thickness	0.070mm



DOUBLE SIDED POLYESTER TAPE

PRODUCT DESCRIPTION

- Manufactured from polyester film coated with synthetic rubber adhesive on silicone release paper

FEATURES / APPLICATIONS

- Aggressive tack and adhesion to various substrates especially plastic surface
- For general bonding and stationery use

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	1000g/25mm
Total Thickness	0.100mm



DOUBLE SIDED PE WHITE FOAM TAPE

PRODUCT DESCRIPTION

- Both sides of polyethylene foam coated with synthetic rubber adhesive which provided high adhesion and shear strength

FEATURES / APPLICATIONS

- Versatile for mounting light objects on wide variety of surfaces
- General purpose mounting tape for indoor application

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	1000g/25mm
Total Thickness	1.000mm

COLORS AVAILABLE
Carrier
Release Liner



DOUBLE SIDED PE BLACK FOAM TAPE

PRODUCT DESCRIPTION

- Both sides of polyethylene foam coated with acrylic adhesive which provided high adhesion and shear strength

FEATURES / APPLICATIONS

- Versatile for mounting light objects on wide variety of surfaces
- Outstanding weather resistance for outdoor use

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	1000g/25mm
Total Thickness	1.000mm

COLORS AVAILABLE
Carrier
Release Liner



DOUBLE SIDED EVA FOAM TAPE

PRODUCT DESCRIPTION

- Both sides of EVA foam coated with synthetic rubber adhesive

FEATURES / APPLICATIONS

- Excellent adhesion to metal and plastic surface and easy application to curved surface
- Suitable for external and internal auto accessories, ultra wide moulding, wheel hub covers, spoilers and brake lights

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	2000g/25mm
Total Thickness	1.500mm

COLORS AVAILABLE
Carrier
Release Liner



ACRYLIC FOAM TAPE

PRODUCT DESCRIPTION

- Manufactured from acrylic adhesive coated directly on release liner that provided quick adhesive strength that builds high bond for long term performance

FEATURES / APPLICATIONS

- Compatible with most plastic surfaces and low surface paint systems
- Recommended for many automotive, electronic and other demanding applications

TECHNICAL CHARACTERISTICS :-

Grade	Transparent	Grey
Peel Adhesion to Steel	2000g/25mm	3000g/25mm
Total Thickness	1.000mm	0.800mm

COLORS AVAILABLE
Carrier TR
PE Liner



FLOOR MARKING TAPE HAZARD WARNING TAPE

PRODUCT DESCRIPTION

- Soft PVC coated with rubber adhesive in excellent plasticity and rigidity can be used both indoor and outdoor

FEATURES / APPLICATIONS

- Ideal for floor / lane marking, hazard warning, identifying safety caution areas or decoration, even for sealing, bundling and colour applications
- Excellent abrasion resistance to acid, alkaline and oil

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	400g/25mm
Total Thickness	0.150mm

COLORS AVAILABLE

- Floor Marking Tape ● ● ● ●
- Hazard Warning Tape ● ●
- Hazard Warning Tape ● ●



HARD PVC TAPE

PRODUCT DESCRIPTION

- Hard PVC backing coated with rubber based adhesive

FEATURES / APPLICATIONS

- The structure of PVC backing ensures excellent plasticity and rigidity
- Ideal for easy identification and bag sealing

TECHNICAL CHARACTERISTICS :-

Total Thickness	0.050mm
-----------------	---------

COLORS AVAILABLE

- ● ● ●



LITHOGRAPHIC TAPE

PRODUCT DESCRIPTION

- Manufactured from red cellulose film coated with rubber based adhesive. The red film is specially formulated to minimize transmission of UV light during photographic masking usage

FEATURES / APPLICATIONS

- For indoor as lithographic masking by photographic plate makers, printers, flexo and gravure converters, engravers of printing and embossing plates and cylinder, screen printers and printed circuit manufacturer

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	250g/12mm
Holding Power	1440 mins
Total Thickness	0.055mm

OPP TAPE (PLAIN & PRINTED)

PRODUCT DESCRIPTION

- Biaxially oriented polypropylene (OPP) transparent film coated with acrylic based adhesive in various colours
- Biaxially oriented polypropylene (OPP) transparent film coated with synthetic rubber based adhesive for hot melt

FEATURES / APPLICATIONS

- Packaging tape for medium and heavy carton sealing
- Can be used in conjunction with both automatic application and hand dispensers
- Available in printed form for security, advertising and handling instruction

TECHNICAL CHARACTERISTICS :-

Grade	Emulsion Acrylic	Solvent Acrylic	Hot Melt
Peel Adhesion to Steel	300g/25mm	400g/25mm	1000g/25mm
Total Thickness	0.045mm	0.045mm	0.048mm

COLORS AVAILABLE

- ● ● ● ●



SOFT PVC INSULATING TAPE

PRODUCT DESCRIPTION

- Soft plasticized PVC tape coated with solvent rubber based adhesive

FEATURES / APPLICATIONS

- Used primarily for electrical insulation purpose with excellent resistance to abrasion and weather
- Good voltage resistance suitable for wire and cable insulation or repairs, sealing, protection or colour coding

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	200g/18mm
Total Thickness	0.105mm

COLORS AVAILABLE

- ● ● ● ●



SILICONISED KRAFT PAPER TAPE

PRODUCT DESCRIPTION

- Siliconised brown kraft paper coated with synthetic rubber based adhesive

FEATURES / APPLICATIONS

- Used for packaging, bundling and general sealing applications
- For cold climate and freezer condition packaging

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	1000g/25mm
Total Thickness	0.130mm

STATIONERY TAPE

PRODUCT DESCRIPTION

- Biaxially oriented polypropylene transparent film coated with acrylic based adhesive, ideal for wide range of uses, strong yet tears easily by hand when required

FEATURES / APPLICATIONS

- Used mainly in home or office for mending, gift wrapping and sealing of light weight boxes
- Outstanding shelf life due to non ageing characteristics and moisture resistant

TECHNICAL CHARACTERISTICS :-

Peel Adhesion to Steel	320g/25mm
Total Thickness	0.043mm



VENEER EDGE TAPE VENEER PERFORATED TAPE

PRODUCT DESCRIPTION

- Kraft paper backing coated with water based adhesive

FEATURES / APPLICATIONS

- Widely used during the process of manufacturing plywood
- Consistently good adhesion when applied to plywood despite variations in the water content of the veneers

TECHNICAL CHARACTERISTICS :-

Grade	Veneer Edge Tape	Veneer Perforated Tape
Peel Adhesion to Steel	220g/12mm(wet)	400g/18mm(dry)
Total Thickness	0.095-0.100mm	0.095-0.100mm



DISPENSERS & OTHERS

DISPENSERS AVAILABLE

- CELLULOSE TAPE DISPENSER
- CUT BAG SEALER
- GUMMED PAPER TAPE DISPENSER
- MULTIROLL TAPE DISPENSER
- OPP TAPE DISPENSER

OTHERS

- SILVER DUCT TAPE
- STRETCH FILM
- TEFLON TAPE



For latest information on our products, please visit www.loytape.com.my

