



PRODUCT INFORMATION

Product **Gummed Paper Tape**
Printed Gummed Paper Tape
Reinforced Gummed Paper Tape
Printed Reinforced Gummed Paper Tape

Brand Loytape, Star

Product Description Gummed Paper Tape is water-based glue with kraft paper backing for ecologically friendly carton sealing. Reinforced Gummed Paper Tape of kraft paper backing with reinforced fibre is specially for heavy duty carton sealing. Printed Gummed Paper Tape and Printed Reinforced Gummed Paper Tape also available.

Construction

Backing	- Kraft paper, Reinforced kraft paper
Adhesive	- Water based adhesive
Colour	- Brown (for Reinforced Gummed Paper Tape) / White, Brown (for Gummed Paper Tape)

Sizes

Standard Widths	24 mm, 36 mm, 48 mm, 60 mm, 72 mm
Standard Lengths	55 yards (Gummed Paper Tape), 90 m, 180 m (Reinforced Gummed Paper Tape)
Core size (ID)	1 3/4 inch and 2 inch

Packing	Gummed Paper Tape		Printed Gummed Paper Tape	
	Width x Length	Rolls/Carton	Width x Length	Rolls/Carton
	24 mm x 55 yards	72	48 mm x 100 m	15
	36 mm x 55 yards	48	60 mm x 100 m	12
	48 mm x 55 yards	36	72 mm x 100 m	10
	60 mm x 55 yards	30		
	72 mm x 55 yards	24		

Packing	Reinforced Gummed Paper Tape		Printed Reinforced Gummed Paper Tape	
	Width x Length	Rolls/Tube	Width x Length	Rolls/ Tube
	48 mm x 90 m	15	48 mm x 100 m	15
	60 mm x 90 m	12	60 mm x 100 m	12
	72 mm x 90 m	10	72 mm x 100 m	10
	48 mm x 180 m	6		
	60 mm x 180 m	5		
	72 mm x 180 m	4		

Physical Properties

Dry Tack (Both products)	350 g/25 mm
Total thickness	
- Gummed Paper Tape	0.120 mm
- Reinforced Gummed Paper Tape	0.130 mm

The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.

Features

Quick and easy application.
Sticks securely on carton regardless of temperature variation.
Available in printed form for security, advertising and handling instruction.

Storage Condition To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.

Important Notice Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.

Manufactured under Loytape strict quality system registered under ISO 9001

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

Branches	Address	Tel No	Fax No	E-mail	Date of Issue : 2017
Penang	1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.	604-3907049	604-3997561	sales-pg@loytape-marketing.com.my	
Kuala Lumpur	31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.	603-92008199	603-92007990 / 8990	sales-kl@loytape-marketing.com.my	
Johor Bahru	11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor.	607-3559968	607-3559967	sales-jb@loytape-marketing.com.my	
Ipoh	10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.	605-5365916	605-5362717	sales-ipoh@loytape-marketing.com.my	

Corporate Office

Loytape Industries Sdn Bhd : 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang, Malaysia.

604-3907049

604-3993030

stick2us@loytape.com.my