



## PRODUCT INFORMATION

### Product **Masking Tape (High Temperature ) MKT- 06**

**Brand** Loytapes

**Product Description** MKT- 06 High Temperature Masking Tape is specially suited for high temperature bandoleering application for the electronics industry.

**Construction**

|          |   |
|----------|---|
| Backing  | - Crepe paper treated with heat resistant saturant      |
| Adhesive | - Rubber based pressure sensitive cured adhesive system |
| Colour   | - Buff  |

**Sizes**

|                  |  |
|------------------|--|
| Standard widths  | 12 mm, 18 mm, 24 mm, 36 mm, 48 mm, 60mm, 72mm  |
| Standard lengths | 45m  |
| Core size (ID)   | 3 inch (Equivalent to 76 mm)   |
| Special sizes    | Customised width and length available on request subject to minimum order quantity.<br>Jumbo roll in width of 1500 mm available. |

| Packing | Width x length | Rolls/Carton |
|---------|----------------|--------------|
|         | 12 mm x 45 m   | 144          |
|         | 18 mm x 45 m   | 96           |
|         | 24 mm x 45 m   | 72           |
|         | 36 mm x 45 m   | 48           |
|         | 48 mm x 45 m   | 36           |
|         | 60 mm x 45 m   | 30           |
|         | 72 mm x 45 m   | 24           |

**Physical Properties**

|                        |                        |
|------------------------|------------------------|
| Peel adhesion to steel | 920 g/ 25 mm           |
| Total thickness        | 0.165 mm               |
| Heat resistance        | Up to 160°C for 1 hour |

The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.

**Features**

- Good crepe backing with natural rubber cured adhesive for excellent holding strength to prevent lifting.
- Soft crepe backing allows masking to wrap around target object.
- Sticks to a wide variety of surfaces.
- No tacky residue left on surface when removed

**Storage Condition** To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.

**Important Notice** Loytapes Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.

Manufactured under Loytapes ® strict quality system registered under ISO 9001

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

| Branches         | Address   | Tel No       | Fax No              | E-mail                               |
|------------------|---|--------------|---------------------|--------------------------------------|
| Penang           | 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.      | 604-3907049  | 604-3997561         | sales-pg@loytapes-marketing.com.my   |
| Kuala Lumpur     | 31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.           | 603-92008199 | 603-92007990 / 8990 | sales-kl@loytapes-marketing.com.my   |
| Johor Bahru      | 11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor. | 607-3559968  | 607-3559967         | sales-jb@loytapes-marketing.com.my   |
| Ipoh             | 10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.          | 605-5365916  | 605-5362717         | sales-ipoh@loytapes-marketing.com.my |
| Corporate Office |   |              |                     |                                      |