



PRODUCT INFORMATION

Product **OPP Tape / Printed OPP Tape**

Brand Loytape, Star, Star 2000, No.1

Product Description OPP Tape is a moderate tack adhesive tape of biaxially orientated polypropylene (OPP) backing widely used for carton sealing.
Printed OPP tape also available

Construction
 Backing - Biaxially orientated polypropylene (OPP)
 Adhesive - Emulsion Acrylic or Solvent Acrylic Based Adhesive
 Colour - Brown, Transparent, Blue, Green, Red, Yellow, White

Sizes
 Standard widths 24 mm, 36 mm, 48 mm, 60 mm, 72 mm
 Standard lengths 40 yards, 40 m, 80 yards, 1000 m
 Core size (ID) 3 inch (Equivalent to 76 mm)
 Special sizes Customize printed OPP tape is available on request, subject to minimum order quantity.

| Packing | Emulsion Acrylic | | Solvent Acrylic | |
|---------|------------------|--------------|-----------------|--------------|
| | Width x Length | Rolls/Carton | Width x Length | Rolls/Carton |
| | 24 mm x 40 yards | 240 | 24 mm x 40 m | 240 |
| | 36 mm x 40 yards | 160 | 36 mm x 40 m | 160 |
| | 48 mm x 40 yards | 120 | 48 mm x 40 m | 120 |
| | 60 mm x 40 yards | 100 | 60 mm x 40 m | 100 |
| | 72 mm x 40 yards | 80 | 72 mm x 40 m | 80 |
| | 48 mm x 80 yards | 72 | 48 mm x 1000 m | 6 |

Physical Properties
 Peel adhesion to steel
 - Emulsion Acrylic 300 g/25 mm
 - Solvent Acrylic 400 g/25 mm
 - Hot Melt 1000 g/25 mm

 Total thickness
 - Emulsion Acrylic 0.045 mm
 - Solvent Acrylic 0.045 mm
 - Hot Melt 0.048 mm

The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.

Features
 High tacky adhesive assures a tight bond onto carton box.
 Good impact resistance arising from the high tensile strength of OPP film.
 Neat and easy to apply.
 Soft and conformable.
 Printed OPP available.

Storage Condition To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.

Important Notice Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.

Manufactured under Loytape strict quality system registered under ISO 9001

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

| Branches | Address | Tel No | Fax No | E-mail | Date of Issue : 2017 |
|------------------|---|--------------|---------------------|-------------------------------------|----------------------|
| Penang | 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang. | 604-3907049 | 604-3997561 | sales-pg@loytape-marketing.com.my | |
| Kuala Lumpur | 31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur. | 603-92008199 | 603-92007990 / 8990 | sales-kl@loytape-marketing.com.my | |
| Johor Bahru | 11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor. | 607-3559968 | 607-3559967 | sales-jb@loytape-marketing.com.my | |
| Ipoh | 10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak. | 605-5365916 | 605-5362717 | sales-ipoh@loytape-marketing.com.my | |
| Corporate Office | | | | | |