



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : CELLULOSE TAPE

PRODUCT CODE : CT

FEATURES

- Cellulose film coated with rubber based adhesive.
- The transparent tape is easy tear; smooth dispensing with good finger tack and moderate adhesion.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 550
2.	Adhesive Coating Weight	gsm	14 ± 3
3.	Total Thickness	mm	0.044 / 0.049
4.	Holding Power	mins	Min 1440
5.	Temperature Range	°C	Ambient

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	Cellulose film
2.	Basic Weight	40gsm / 45 gsm
3.	Colour	Transparent

APPLICATION AND USAGE

- Recommended for indoor stationery use for closing and sealing of small box / plastic bag, mending torn documents and general stationery taping.
- Most suitable for hamper wrapping.
- Can be used as antistatic tape.

LAB TEST CONDITIONS

Temperature : 20 ± 5 °C
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 deg °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.