



**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

## TECHNICAL INFORMATION

**PRODUCT NAME : DOUBLE SIDE PE WHITE FOAM TAPE**

**PRODUCT CODE : WFT**

### FEATURES

- Both sides of polyethylene foam coated with synthetic rubber adhesive.
- Excellent adhesion to metal and plastic surface.
- Easy application to curved surfaces.

### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Strength (ATS)	g/25mm	<b>Min 1000</b>
2.	Total Thickness	mm	<b>1.0 (1/25")</b>
3.	Holding Power	hrs	<b>Min 12</b>
4.	Service Temperature Range	°C	<b>10 - 80</b>

### PROPERTIES OF RAW MATERIAL

No.	Particular	Description
1.	Carrier material	<b>PE closed cell foam</b>
2.	Carrier colour	<b>White</b>
3.	Release liner	<b>Silicone paper</b>

### APPLICATION AND USAGE

- The foam tapes can be used as versatile mounting tapes for the mounting of light objects.
- Mounting lead on the alloy wheels.
- General purpose mounting tape in in-door application.

### LAB TEST CONDITIONS

Temperature : 20 ± 5 °C  
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Dec 2016**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.