



**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

## TECHNICAL INFORMATION

**PRODUCT NAME : HARD PVC TAPE**

**PRODUCT CODE : HPVC**

### FEATURES

- The structure of the PVC backing guarantees excellent plasticity and rigidity.
- The thick layer of adhesive gives this tape a high tack quality which can be used on a wide number of surfaces for easy identification and also can be used in confectionary industry.

### TECHNICAL CHARACTERISTICS

No.	Item	Unit	Typical Value
1.	Carrier Thickness	mm	0.030
2.	Total Thickness	mm	0.050
3.	Heat Resistance	° C	65

### APPLICATION AND USAGE

- Application for easy identification.
- Application for bag sealing.

### STORAGE CONDITIONS

Temperature : 20 +- 5 ° C  
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Dec 2016**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.