



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai , Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : MASKING TAPE (for Bandoleering)

PRODUCT CODE : MKT-06

FEATURES

- Premium crepe masking tape with excellent adhesion and tack.
- Good resistance to solvent, oil and water, makes it an excellent choice for demanding industrial application.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 920
2.	Adhesive Coating Weight	g/m ²	47 ± 3
3.	Total Thickness	mm	0.165
4.	Solvent Resistance	-	Average
5.	Heat Resistance	1 hr, °C	160

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	Crepe paper
2.	Basic Weight	58 gsm
3.	Colour	Buff

APPLICATION AND USAGE

- For high temperature masking application such as bandoleering and electroplating.
- Heat resistance at 160 °C for 1 hour.

LAB TEST CONDITIONS

Temperature : 20 +- 5 °C

Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE : 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.