



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : SILICONISED KRAFT PAPER TAPE

PRODUCT CODE : SKPT

FEATURES

- Siliconised brown kraft paper tape coated with synthetic rubber adhesive.
- For packaging, bundling and general sealing applications.
- Very good adhesion to various substrates and has low temperature performance.

TECHNICAL CHARACTERISTICS

No.	Item	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 1000
2.	Total Thickness	mm	0.130
3.	Tensile Strength	kg/15mm	6
4.	Backing Material	-	Kraft paper

APPLICATION AND USAGE

- Recommended for wide variety of packaging and bundling operations.
- For cold climate and freezer condition packaging.

LAB TEST CONDITIONS

Temperature : 20 +- 5 ° C

Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.