



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : SOFT SPVC TAPE

PRODUCT CODE : SPVC

FEATURES

- Plasticized PVC tape coated with solvent rubber adhesive.
- Available in various colours and types.
- Good voltage resistance suitable for wire and cable insulation or repairs, sealing, protection or colour coding.

TECHNICAL CHARACTERISTICS

No.	Item	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/18mm	Min 200
2.	Total Thickness	mm	0.105
3.	Tensile Strength	kg/15mm	3.6 +- 1.2
4.	Elongation at Break	%	More than 100

STORAGE CONDITIONS :

Temperature : 20 +- 5 ° C
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.