



**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

## TECHNICAL INFORMATION

**PRODUCT NAME : UV RESISTANT MASKING TAPE**

**PRODUCT CODE : MKT-29 ( Green / Blue / Violet)**

### FEATURES

- Excellent UV resistance.
- The tape is coated with specially formulated solvent acrylic adhesive system.
- Good performance for variety of application that require easy removal without surface damage.

### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	<b>Min 200</b>
2.	Tack Rolling Ball	Ball no.	<b>Min 8</b>
3.	Adhesive Coating Weight	g/m <sup>2</sup>	<b>38 - 45</b>
4.	Total Thickness	mm	<b>0.155</b>
5.	Solvent Resistance	-	<b>Above average</b>
6.	Tensile Strength	kg/15mm	<b>Min 5</b>
7.	Water Resistance	-	<b>Average</b>

### PROPERTIES OF RAW MATERIAL

No.	Particular	Carrier
1.	Type	<b>Crepe Paper</b>
2.	Basic Weight	<b>70 gsm</b>
4.	Colour	<b>Green for 7 days / Blue for 14 days / Violet for 30 days</b>

### APPLICATION AND USAGE

- This premium tape is used for masking application on glass, vinyl and wood where clean removal is required after expose to direct sunlight.

### LAB TEST CONDITIONS

Temperature : 20 +- 5 ° C  
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Dec 2016**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.