



**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

## TECHNICAL INFORMATION

**PRODUCT NAME : DOUBLE SIDED EVA FOAM TAPE ( WHITE / BLACK)**

**PRODUCT CODE : WFT (EVA) / BFT (EVA)**

### FEATURES

- EVA foam double sides coated with synthetic adhesive.
- The tape gives excellent adhesion to metal and plastic surface, and easy application to curved surfaces.

### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Strength (ATS)	g/25mm	<b>Min 2000</b>
2.	Total Thickness	mm	<b>1.5 ± 10%</b>
3.	Holding Power	hrs	<b>Min 20</b>
4.	Carrier Colour	-	<b>White / Black</b>
5.	Release Liner	-	<b>Green /Yellow Release Liner</b>
6.	Service Temperature Range	°C	<b>100</b>

### APPLICATION AND USAGE

- The tape is specially designed for external and internal auto accessories, moulding, wheel hub covers, spoilers, brake lights, stationery, die cut, impact preventing materials.
- Good holding power and strong adhesion.

### LAB TEST CONDITIONS

Temperature : 20 ± 5 °C  
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Mar 2020**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.