

**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : REINFORCED GUMMED PAPER TAPE

PRODUCT CODE : RGPT

FEATURES

- Cross-ply fabric reinforced paper tape coated with extra thick glue line that offers very high set glue and paper strength when used.
- Store in dry condition.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Coating Weight	gsm	38 ± 7
2.	Total Thickness	mm	Min 0.130
3.	Dry Tack	g/25mm	Min 350
4.	Surface Moisture	%	15.0 ± 5.0
5.	Open Time	sec	Max 13
6.	Rupture Area	%	Min 95
7.	Temperature Range	°C	Ambient

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	Reinforced Brown Kraft Paper
2.	Basic Weight	113 gsm
3.	Colour	Brown

APPLICATION AND USAGE

- Heavy duty paper carton sealing.

LAB TEST CONDITIONS

Temperature : 20 ± 5 °C
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Mar 2020

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.