



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : DOUBLE SIDED POLYESTER TAPE

PRODUCT CODE : DST(P)

FEATURES

- Polyester based double sided tape is specially developed for general bonding and stationery uses.
- It has an aggressive tack and adhesion to various substrates especially plastic surfaces.

TECHNICAL CHARACTERISTICS

No.	Item	Unit	Typical Value
1.	Peel Strength (ATS)	g/25mm	Min 1000
2.	Total Thickness	mm	0.100
3.	Holding Power	hrs	Min 12
4.	Solvent Resistance	-	Average
6.	Service Temperature Range	°C	10 ~ 100

PROPERTIES OF RAW MATERIAL

No.	Particular	Description
1.	Carrier Material	Polyester
2.	Carrier Colour	Transparent
3.	Release Liner	Silicone release paper

STORAGE CONDITIONS :

Temperature : 20 +- 5 °C
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Mar 2020

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.