



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : STATIONERY TAPE

PRODUCT CODE : STE

FEATURES

- Biaxially oriented polypropylene transparent film coated with acrylic adhesive, idea for wide range of uses, strong yet tears easily by hand when required.
- It can be used in conjunction with both automatic machinery application and hand dispenser.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 320
2.	Total Thickness	mm	0.043 ± 0.004
3.	Solvent Resistance	-	Average
4.	Temperature Range	° C	Ambient to < 60 ° C

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier Material	Biaxially Oriented Polypropylene
2.	Raw Film Thickness	0.025mm
3.	Colour	Transparent with yellowish tinge

APPLICATION AND USAGE

- Packaging tape for general industrial use packaging application, bundling and carton sealing purpose.
- Lamination use not recommended.

LAB TEST CONDITIONS

Temperature : 20 ± 5 ° C
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Mar 2020

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.