



**PRODUCT INFORMATION**

**Product** **OPP Tape / Printed OPP Tape**

**Brand** Loytape, Star, Star 2000, No.1

**Product Description** OPP Tape is a moderate tack adhesive tape of biaxially orientated polypropylene (OPP) backing widely used for carton sealing.  
Printed OPP tape also available

**Construction**  
 Backing - Biaxially orientated polypropylene (OPP)  
 Adhesive - Emulsion Acrylic or Solvent Acrylic Based Adhesive  
 Colour - Brown, Transparent, Blue, Green, Red, Yellow, White

**Sizes**  
 Standard widths 24 mm, 36 mm, 48 mm, 60 mm, 72 mm  
 Standard lengths 40 yards, 40 m, 80 yards, 1000 m  
 Core size (ID) 3 inch (Equivalent to 76 mm)  
 Special sizes Customize printed OPP tape is available on request, subject to minimum order quantity.

Packing	Emulsion Acrylic		Solvent Acrylic	
	Width x Length	Rolls/Carton	Width x Length	Rolls/Carton
	24 mm x 40 yards	240	24 mm x 40 m	240
	36 mm x 40 yards	160	36 mm x 40 m	160
	48 mm x 40 yards	120	48 mm x 40 m	120
	60 mm x 40 yards	100	60 mm x 40 m	100
	72 mm x 40 yards	80	72 mm x 40 m	80
	48 mm x 80 yards	72	48 mm x 1000 m	6

**Physical Properties**  
 Peel adhesion to steel  
 - Emulsion Acrylic 300 g/25 mm  
 - Solvent Acrylic 400 g/25 mm  
 - Hot Melt 1000 g/25 mm  
  
 Total thickness  
 - Emulsion Acrylic 0.045 mm  
 - Solvent Acrylic 0.045 mm  
 - Hot Melt 0.048 mm

The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.

**Features**  
 High tacky adhesive assures a tight bond onto carton box.  
 Good impact resistance arising from the high tensile strength of OPP film.  
 Neat and easy to apply.  
 Soft and conformable.  
 Printed OPP available.

**Storage Condition** To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.

**Important Notice** Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.

Manufactured under Loytape strict quality system registered under ISO 9001

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

Branches	Address	Tel No	Fax No	E-mail
Penang	1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.	604-3907049	604-3997561	sales-pg@loytape-marketing.com.my
Kuala Lumpur	31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.	603-92008199	603-92007990 / 8990	sales-kl@loytape-marketing.com.my
Johor Bahru	11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor.	607-3559968	607-3559967	sales-jb@loytape-marketing.com.my
Ipoh	10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.	605-5365916	605-5362717	sales-ipoh@loytape-marketing.com.my

Corporate Office

Loytape Industries Sdn Bhd : 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang, Malaysia.

604-3907049

604-3993030

[stick2us@loytape.com.my](mailto:stick2us@loytape.com.my)

Date of Issue : 2017