



## PRODUCT INFORMATION

|                            |  |  |
|----------------------------|--|--|
| <b>Product</b>             | <b>Siliconised Brown Kraft Paper Tape</b>  |  |
| <b>Brand</b>               | Star, Star2000   |  |
| <b>Product Description</b> | Siliconised brown kraft paper coated with synthetic rubber based adhesive  |  |
| <b>Construction</b>        | Backing  | - Siliconised kraft paper                          |
|                            | Adhesive   | - Pressure sensitive specially formulated adhesive |
|                            | Colour   | - Brown  |
| <b>Sizes</b>               | Standard widths  | 24mm, 36mm, 48 mm, 60mm, 72mm                      |
|                            | Standard lengths   | 22 m   |
|                            | Core size (ID)   | 3 inch (Equivalent to 76 mm)                       |
| <b>Packing</b>             | <b>Width x Length</b>  | <b>Rolls/Carton</b>                                |
|                            | 24 mm x 22 m   | 144  |
|                            | 36 mm x 22 m   | 96   |
|                            | 48 mm x 22 m   | 72   |
|                            | 60 mm x 22 m   | 60   |
|                            | 72 mm x 22 m   | 48   |
| <b>Physical Properties</b> | Peel adhesion to steel   | 1000 g/25 mm                                       |
|                            | Total thickness  | 0.130 mm   |
|                            | The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.   |  |
| <b>Features</b>            | Good adhesion to various substrates.<br>Used for packaging, bundling and general sealing applications<br>Suitable for cold climate and freezer condition packing   |  |
| <b>Storage Condition</b>   | To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.  |  |
| <b>Important Notice</b>    | Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications. |  |
|                            | Manufactured under Loytape strict quality system registered under ISO 9001   |  |

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

| Branches         | Address   | Tel No       | Fax No              | E-mail                              | Date of Issue : 2017 |
|------------------|---|--------------|---------------------|-------------------------------------|----------------------|
| Penang           | 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.      | 604-3907049  | 604-3997561         | sales-pg@loytape-marketing.com.my   |                      |
| Kuala Lumpur     | 31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.           | 603-92008199 | 603-92007990 / 8990 | sales-kl@loytape-marketing.com.my   |                      |
| Johor Bahru      | 11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor. | 607-3559968  | 607-3559967         | sales-jb@loytape-marketing.com.my   |                      |
| Ipoh             | 10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.          | 605-5365916  | 605-5362717         | sales-ipoh@loytape-marketing.com.my |                      |
| Corporate Office |   |              |                     |                                     |                      |