



## PRODUCT INFORMATION

|                            |   |   |
|----------------------------|---|---|
| <b>Product</b>             | <b>Cellulose Tape</b>   |   |
| <b>Brand</b>               | Loytape , Star  |   |
| <b>Product Description</b> | Cellulose tape is manufactured from transparent cellulose film, which is a wood based product of regenerated pulp. Cellulose tape is highly transparent and has a pressure sensitive rubber adhesive system.  |   |
| <b>Construction</b>        | Backing   | - High quality super clear cellulose film   |
|                            | Adhesive  | - Pressure sensitive specially formulated rubber adhesive system  |
|                            | Colour  | - Clear transparent   |
| <b>Sizes</b>               | Standard widths   | 12 mm, 18 mm, 24 mm   |
|                            | Standard lengths  | 2.5 m, 15 yards, 30 yards, 40 m   |
|                            | Core size (ID)  | 1 inch, 3 inch (Equivalent to 25 mm, 76 mm)   |
|                            | Special sizes   | Customised width and length available on request subject to minimum order quantity.<br>Jumbo roll in width of 750 mm available. |
| <b>Packing</b>             | <b>Width x Length</b>   | <b>Rolls/Carton</b>   |
|                            | 12mm x 2.5 m  | 1440  |
|                            | 12mm x 15 yards   | 288   |
|                            | 18mm x 15 yards   | 192   |
|                            | 24mm x 15 yards   | 144   |
|                            | 12 mm x 30 yards  | 144   |
|                            | 18mm x 30 yards   | 96  |
|                            | 24mm x 30 yards   | 72  |
|                            | 12mm x 40 m   | 144   |
|                            | 18mm x 40 m   | 96  |
|                            | 24 mm x 40 m  | 72  |
| <b>Physical Properties</b> | Peel adhesion to steel  | 550 g/25 mm   |
|                            | Holding power   | 1440 mins   |
|                            | Total thickness   | 0.044 - 0.049 mm  |
|                            | The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.  |   |
| <b>Features</b>            | Suitable for hamper wrapping, gift wrapping, sealing of plastic bags, small boxes and light weight cartons.<br>Easy tear<br>Backing using ecological friendly material (cellulose film)<br>Transparent and can read through<br>Sticks on most surfaces<br>Suitable for application as antistatic tape |   |
| <b>Application</b>         | Cellulose tape can be hand held or dispensed with wide varieties of dispensers to facilitate the application of cellulose tape.   |   |
| <b>Storage Condition</b>   | To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.   |   |
| <b>Important Notice</b>    | Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.                    |   |
|                            | Manufactured under Loytape strict quality system registered under ISO 9001  |   |

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

| Branches     | Address   | Tel No       | Fax No              | E-mail                              | Date of Issue : 2017 |
|--------------|---|--------------|---------------------|-------------------------------------|----------------------|
| Penang       | 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.      | 604-3907049  | 604-3997561         | sales-pg@loytape-marketing.com.my   |                      |
| Kuala Lumpur | 31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.           | 603-92008199 | 603-92007990 / 8990 | sales-kl@loytape-marketing.com.my   |                      |
| Johor Bahru  | 11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor. | 607-3559968  | 607-3559967         | sales-jb@loytape-marketing.com.my   |                      |
| Ipoh         | 10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.          | 605-5365916  | 605-5362717         | sales-ipoh@loytape-marketing.com.my |                      |

Corporate Office

Loytape Industries Sdn Bhd : 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang, Malaysia.

604-3907049

604-3993030

[stick2us@loytape.com.my](mailto:stick2us@loytape.com.my)