



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : MASKING TAPE YELLOW

PRODUCT CODE : MKT-05(Y)

FEATURES

- Premium yellow crepe masking tape exhibit excellent adhesion, tack and good cohesion strength.
- Specially formulated rubber based adhesive for high temperature application.
- Good resistance to solvent, oil and water.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 850
2.	Tack Rolling Ball	ball no.	Min 8
3.	Adhesive Coating Weight	g/m ²	45 ± 4
4.	Total Thickness	mm	0.155
5.	Solvent Resistance	-	Good
6.	Heat Resistance	1 hr, °C	150

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	Crepe Paper
2.	Basic Weight	60 gsm
3.	Colour	Yellow

APPLICATION AND USAGE

- This premium tape is used for high temperature masking application such as automotive paint spraying, bandoleering and electroplating.
- Heat resistance at 150 °C for 1 hour.

LAB TEST CONDITIONS

Temperature : 20 ± 5 °C

Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.

