



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : MASKING TAPE

PRODUCT CODE : MKT-01

FEATURES

- The crepe masking tape exhibits high adhesion, high cohesion and high holding power.
- Specially formulated adhesive allows no tacky residue on surface when removed.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 600
2.	Tack Rolling Ball	ball no.	Min 5
3.	Adhesive Coating Weight	g/m ²	34 ± 5
4.	Total Thickness	mm	0.135
5.	Holding Power	mins	Min 1440
6.	Solvent Resistance	-	Average
7.	Heat Resistance	1 hr, °C	80

PROPERTIES OF RAW MATERIAL

No.	Particular	
1.	Carrier	Crepe Paper
2.	Basic Weight	55 gsm
3.	Colour	Buff

APPLICATION AND USAGE

- A general purpose masking tape used for various masking, holding, bundling and sealing light to medium paper carton packaging. For industrial, home and office use.
- Heat resistance at 80 °C for 1 hour.

LAB TEST CONDITIONS

Temperature : 20 ± 5 °C

Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.