



**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

## TECHNICAL INFORMATION

**PRODUCT NAME : ACRYLIC FOAM TAPE – GREY (0.8mm)**

**PRODUCT CODE : DSAFT( grey)**

### FEATURES

- The double sided acrylic foam tape provides a unique adhesive system that provided quick adhesive strength that builds high bond for long term performance.
- The tape is compatible with most plastics and low surface paint systems.
- It provides weather and solvent resistance.
- Recommended for many Automotive, Electronic and other demanding applications.

### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Strength (ATS)	g/25mm	<b>Min 3000</b>
2.	Total Thickness	mm	<b>0.8 ± 10%</b>
3.	Holding Power	hrs	<b>Min 24</b>
4.	Carrier Colour	-	<b>Grey</b>
5.	Release Liner	-	<b>Red PE Liner</b>
6.	Service Temperature Range	°C	<b>-20 to 120</b>

### APPLICATION AND USAGE

- Good holding power and strong adhesion for metals.
- Good performance for die –cutting
- Good performance to bond LCD + polycarbonate panel
- Various plastic panel fixing

### LAB TEST CONDITIONS

Temperature : 20 ± 5 °C  
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Dec 2016**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.