



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : ALUMINIUM FOIL TAPE

PRODUCT CODE : AFT

FEATURES

- A flexible aluminium foil, coated with an aggressive, high tack, high temperature acrylic adhesive system.
- The foil conforms well to fibrous and sheet metal duct, providing an excellent vapour seal.
- The foil also conforms well around corners and to irregular surfaces.
- Recommended for use at elevated temperature.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 500
2.	Total Thickness	mm	0.060
3.	Curing	-	Min AC
4.	Solvent Resistance	-	Average
5.	Applying Temperature	-	+10 to +40
6.	Temperature Resistance	° C	-20 to 120

PROPERTIES OF RAW MATERIAL

No.	Particular	Description
1.	Carrier Material	Bare Aluminium Foil
2.	Foil Thickness	0.026mm
3.	Colour	Bright silver
4.	Release liner	White PE kraft 70gsm

APPLICATION AND USAGE

- Lamination over fiberglass air-conditions ductboard.
- Sealing of cold store installation and packing refrigerated export containers.
- Decoration point of sale media.

LAB TEST CONDITIONS

Temperature : 20 ± 5 ° C
Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.