



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : CLOTH TAPE

PRODUCT CODE : CLT

FEATURES

A polyethylene laminated cloth backing coated with rubber adhesive designed for heavy packing process.

TECHNICAL CHARACTERISTICS

No.	Parameters	Unit	Typical Value
1.	Peel Strength (ATS)	g/25mm	Min 700
2.	Tack Rolling Ball	ball no.	Min 6
3.	Total Thickness	mm	0.250
4.	Mesh	-	70

APPLICATION AND USAGE

Available in many colours suitable for sealing, strapping, marking, decoration identification, book binding and other uses in many fields.

STORAGE CONDITIONS :

Temperature : 20 +- 5 °C
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.