



LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,
Kawasan Perusahaan Perai,
13600 Perai, Seberang Perai, Penang, Malaysia
Tel No. 604-3907049, Fax No. 604-3993030.
E-mail : stick2us@loytape.com.my
Website: www.loytape.com.my

TECHNICAL INFORMATION

PRODUCT NAME : FLOOR MARKING TAPE / HAZARD WARNING TAPE

FEATURES

- Soft PVC coated with rubber adhesive, available with various colours, commonly with stripe printed (yellow/black, red/white, green/white), ideal for floor/lane marking, hazard warning, identifying safety caution areas or decoration, even for sealing, bundling and colour applications.
- The structure of the PVC backing in excellent plasticity and rigidity thus can be used in outdoor and indoor.

TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	Min 400
2.	Total Thickness	mm	0.150
3.	Tack Rolling Ball	Ball no.	Min 3
4.	Elongation at Break	%	150 +- 20%

LAB TEST CONDITIONS

Temperature : 20 +- 5 ° C
Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

SHELF LIFE: 12 MONTHS

Dec 2016

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.