



PRODUCT INFORMATION

Product	Cellulose Tape	
Brand	Loytape , Star	
Product Description	Cellulose tape is manufactured from transparent cellulose film, which is a wood based product of regenerated pulp. Cellulose tape is highly transparent and has a pressure sensitive rubber adhesive system.	
Construction	Backing Adhesive Colour	- High quality super clear cellulose film - Pressure sensitive specially formulated rubber adhesive system - Clear transparent
Sizes	Standard widths Standard lengths Core size (ID) Special sizes	12 mm, 18 mm, 24 mm 2.5 m, 15 yards, 30 yards, 40 m 1 inch, 3 inch (Equivalent to 25 mm, 76 mm) Customised width and length available on request subject to minimum order quantity. Jumbo roll in width of 750 mm available.
Packing	Width x Length 12mm x 2.5 m 12mm x 15 yards 18mm x 15 yards 24mm x 15 yards 12 mm x 30 yards 18mm x 30 yards 24mm x 30 yards 12mm x 40 m 18mm x 40 m 24 mm x 40 m	Rolls/Carton 1440 288 192 144 144 96 72 144 96 72
Physical Properties	Peel adhesion to steel Holding power Total thickness	550 g/25 mm 1440 mins 0.044 - 0.049 mm
The technical information exhibited above represent average values obtained in our laboratory testing only and should not be used for specifications purposes.		
Features	Suitable for hamper wrapping, gift wrapping, sealing of plastic bags, small boxes and light weight cartons. Easy tear Backing using ecological friendly material (cellulose film) Transparent and can read through Sticks on most surfaces Suitable for application as antistatic tape	
Application	Cellulose tape can be hand held or dispensed with wide varieties of dispensers to facilitate the application of cellulose tape.	
Storage Condition	To be stored at room temperature. Keep away from prolonged exposure to direct sunlight.	
Important Notice	Loytape Industries Sdn Bhd does not accept any responsibility directly or indirectly for any consequential loss or damage as a result of our recommendations. You are hereby advised to conduct your own tests to determine the suitability of the products for your applications.	
Manufactured under Loytape strict quality system registered under ISO 9001		

For Sales within Malaysia, Kindly Contact any of the Branches Nearest to You | (Business Hours : 8.30am - 5.30pm, Mon - Fri)

Branches	Address	Tel No	Fax No	E-mail
Penang	1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang.	604-3907049	604-3997561	sales-pg@loytape-marketing.com.my
Kuala Lumpur	31, Jalan 10/91, Taman Shamelin Perkasa, Cheras, 56100, Kuala Lumpur.	603-92008199	603-92007990 / 8990	sales-kl@loytape-marketing.com.my
Johor Bahru	11, Jalan Austin Perdana 2/23, Taman Austin Perdana, 81100, Johor Bahru, Johor.	607-3559968	607-3559967	sales-jb@loytape-marketing.com.my
Ipoh	10-A, Dataran Tasek Timur 6, Anjung Bercham Utara, 31400, Ipoh, Perak.	605-5365916	605-5362717	sales-ipoh@loytape-marketing.com.my
Corporate Office				

Loytape Industries Sdn Bhd : 1017, Lorong Perusahaan 1, Kawasan Perusahaan Perai, 13600, Perai, Penang, Malaysia.

604-3907049

604-3993030

stick2us@loytape.com.my