

**LOYTAPE INDUSTRIES SDN. BHD.**

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

**TECHNICAL INFORMATION**

**PRODUCT NAME : MASKING TAPE**

**PRODUCT CODE : MKT-01E**

**FEATURES**

- Economical grade crepe masking tape with good adhesion and moderate tack.
- It is for non-critical usage.

**TECHNICAL CHARACTERISTICS**

No.	Type of Testing	Unit	Typical Value
1.	Peel Adhesion (ATS)	g/25mm	<b>Min 600</b>
2.	Adhesive Coating Weight	g/m <sup>2</sup>	<b>28 ± 3.5</b>
3.	Total Thickness	mm	<b>0.130</b>
4.	Solvent Resistance	-	<b>Average</b>
5.	Heat Resistance	1 hr, °C	<b>60</b>

**PROPERTIES OF RAW MATERIAL**

No.	Particular	
1.	Carrier	<b>Crepe Paper</b>
2.	Basic Weight	<b>55 gsm</b>
3.	Colour	<b>Buff</b>

**APPLICATION AND USAGE**

- For various packaging, holding, bundling and non-critical masking purposes.

**LAB TEST CONDITIONS**

Temperature : 20 ± 5 °C

Humidity : 60 ± 10 % RH

Short term storage under transit containers condition at < 60 °C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Mar 2020**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.