



## LOYTAPE INDUSTRIES SDN. BHD.

Lot 1017, Lorong Perusahaan Satu,  
Kawasan Perusahaan Perai,  
13600 Perai, Seberang Perai, Penang, Malaysia  
Tel No. 604-3907049, Fax No. 604-3993030.  
E-mail : stick2us@loytape.com.my  
Website: www.loytape.com.my

### TECHNICAL INFORMATION

**PRODUCT NAME : VENEER EDGE TAPE**

**PRODUCT CODE : VET**

#### FEATURES

- The VET is mainly used in plywood manufacturing.
- Consistently good adhesion when applied to plywood despite variations in the water content of the veneers.
- Good adaptability to automatic packing machine when used for veneer back composer.

#### TECHNICAL CHARACTERISTICS

No.	Type of Testing	Unit	Typical Value
1.	90° Peel Strength (plywood), wet	g/12mm	Min 220
2.	Total Thickness	mm	0.095 - 0.100
3.	Coating Weight	gsm	32 – 34
4.	Water Resistance	-	Good
5.	Moisture Content	%	5

#### PROPERTIES OF RAW MATERIAL

No.	Particular	Description
1.	Carrier material	Kraft paper
2.	Raw paper grammage	53 gsm
3.	Colour	Brown

#### STORAGE CONDITIONS :

1. Store away from moisture.
2. Keep dry in original moisture proof wrapper.
3. Place horizontally on the shelf.

#### LAB TEST CONDITIONS

Temperature : 20 +- 5 ° C

Humidity : 60 +- 10 % RH

Short term storage under transit containers condition at < 60 ° C should not result in any adverse effect to tape properties.

**SHELF LIFE: 12 MONTHS**

**Mar 2020**

The above mentioned data are typical values only. Suggestion for use and final results correspond to our department technical experience but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use. Information is subject to change without notice.